

## Supported Equipment Schedule

The following table outlines the current required Supported System specifications for PharmacyRx™. These Supported System specifications may be updated by McKesson from time to time as may be necessary to maintain the proper operations of PharmacyRx™. Please check to ensure the workstation meets the minimum requirements to run any software in addition to those required by PharmacyRx™. Any other configurations are subject to certification by McKesson.

Component	System Requirements
Operating System	Microsoft® Windows® 10 Pro/LTSC 64 Bit McKesson recommends that Windows updates are enabled for security updates and patches.
Processor	1.8GHz or greater CPU
Memory	4GB RAM or greater for Windows 10 Pro 64 bit
Hard Drive Space	20GB or greater
Pointing Device	Standard Windows® compatible keyboard and mouse
Modem	Optional – only required for faxing and dial-up backup connectivity
Network	100/1000 Mbps – Ethernet Recommend PharmacyRx Preferred Network Configuration (see PharmacyRx Homepage for details) IPv6 is not supported
Display	1024 x 768 resolution
Ports	Client shall ensure the hardware provided has the appropriate number of ports required by the peripherals being connected to the system (see connection type below).
Browser	Internet Explorer 11 (Windows 10 default browser, MS Edge, is not supported)
Java	Java 8 Update 92
Antivirus Software	Client shall be solely responsible for acquiring and maintaining antivirus software and to institute mechanisms to prevent against viral infection of information or other corruption. McKesson recommends that Client run antivirus software that is current with the most recent virus definitions.

## Barcode Scanners

Device Type	Device Manufacturer	Model(s)	Connection Type
Preferred	Zebra Motorola/Symbol/Zebra	All Zebra 2D Models (USB) LI2208, LS2208	USB USB
Supported	Honeywell	Hyperion 1300G, 3800G	USB

## Dot Matrix Printers

Device Type	Device Manufacturer	Model(s)	Connection Type
Supported	Okidata	320 / 320 Turbo / 321	

## Supported Equipment Schedule

## Image Scanners

Device Type	Device Manufacturer	Model(s)	Connection Type
Preferred	Xerox	DocuMate 3125	USB
Third Party Discontinued	Fujitsu	FI-6130	USB

## Laser Printers

Device Type	Device Manufacturer	Model(s)	Connection Type
Preferred	Lexmark Lexmark Lexmark	MS621 Series MS810N Series <sup>1</sup> MS315 <sup>2</sup>	Ethernet, USB Ethernet, USB Ethernet, USB
Supported	Dell	M5200	Ethernet, USB
Third Party Discontinued	Lexmark Lexmark	T640, T642, T644 T650, T652, T654	Ethernet, USB Ethernet, USB
Note – simplex (single side) printing only <sup>1</sup> supports MAR form printing <sup>2</sup> Laser Label printing not supported. Recommended volume less than 50 Rx's daily.			

## Printer Fonts

Device Type	Device Manufacturer	Model(s)	Connection Type
Supported	Intercon Intercon Intercon Pharmex Pharmex Architext Architext Architext	Software Fonts DIMM's Daughter Cards DIMM's Daughter Cards Standard Prescription Set DIMM's Daughter Cards	
Note – Lexmark T Series printers use daughter cards instead of DIMM's			

## Signature Capture

Device Type	Device Manufacturer	Model(s)	Connection Type
Preferred	Verifone	MX915, MX925	Network

## Thermal Printers

Device Type	Device Manufacturer	Model(s)	Connection Type
Preferred	Zebra	GK420D	Ethernet, USB